## Lonati


# LE series WOMEN'S SINGLE CYLINDER LBE45T - LBE5T





## WOMEN'S SINGLE CYLINDER

LBE45T - LBE5T







All images in this brochure are indicative and not binding.

## WOMEN'S SINGLE CYLINDER LBE45T - LBE5T

Electropneumatic single cylinder, 4 feeds machine for pantyhose and leggings in plain knit and/or terry, 1x1 and 3x1 fixed mesh on 4 feeds and T-Band, covered lycra plating, 4 feeds plating, size marks and pneumatic selection on all feeds. Single dial jacks. Electronic device to maintain size at any temperature on the machine.

- ♦ 4 feeds single cylinder machine
- 6 pliers suction unit
- 24 yarn fingers
- Motorized sinkers cap, 2 motors
- ◆ 4 pneumatic stitch cams
- 4 pneumatic selection units on fedds 1,2,3 and 4 for mesh

#### MACHINE DIMENSIONS



Length 60 cm + yarn creel cm 130 Depth 60 cm + yarn creel cm 130 Height 136 cm + yarn creel cm 250

#### **MACHINE WEIGHT**



**CERTIFICATION** 



## WOMEN'S SINGLE CYLINDER LBE45T - LBE5T

#### TECHNICAL DATA

MODEL CYLINDER DIAMETER		GAUGE	NEEDLE THICKNESS
LBE45T (Needle latch 8,7mm)	4" 1/2	24	0.41 mm
LBE5T (Needle latch 8,7mm)	5"	24	0.41 mm

Above data are indicative and not binding.

#### STANDARD DEVICES

- 26 or 40 reels yarn creel;
- Sock ejection hood;
- Yarn waste filter:
- Stepper motor controlled suction valve;
- Rotary or fixed antitwist device;
- 8 yarn sliding sensors;
- Laid-in mechanical device on feed 1 and 3;

#### OPTIONAL DEVICES

- DREAM or DREAM ONE device for stretching socks in ejection
- 2,2 Kw suction fan
- Nautlilus software licence
- Dinema GRYF yarn feeder, 12 max
- Dinema Plus medical or bare elastomer yarn feeders, 4 max
- Yarn sensors, 24 max
- 4 motorized stitch cams
- Motorized plating yarn finger radial movement

#### **SUITABLE YARNS**

The machine is designed to be used with the following yarns:

- Nylor
- Elastomers (bare, single or double cover);
- Filanca;

#### **POSSIBLE KNITTINGS**

The standard machine can perform the following knittings

- Terry
- Plain knit
- 1:1, 3:1, 5:1, 7:1, 1:3 fixed mesh
- 1:1 for vertical bands for cutting
- Supp-hose on 2 or 4 feeds
- Plain knit plating on 2 or 4 feeds

## WOMEN'S SINGLE CYLINDER LBE45T - LBE5T



#### **PERFORMANCES**

	4" 1/2 CYLINDER DIAMETER	5" CYLINDER DIAMETER	
GAUGE	24	24	
KNITTING FEATURES	With terry 400 rpm max speed	With terry 350 rpm max speed	
MAXIMUM SPEED	500RPM	500 RPM	

Above data are indicative and not binding.

#### DISCLAIMER:

Speed may need to be adjusted according to the inclination of the stitch cams, to the mechanical parts in use and to the yarn. N.B. All data in the brochure are for information only and subject to change without any prior notice from Lonati SpA.

#### **ALLOWED PERFORMANCES**

CHART OF MAXIMUM ALLOWED SPEED IN PLAIN KNIT IN RELATION TO THE INCLINATION TO THE STITCH CAMS		
Stitch cam inclination	Maximum allowed speed in plain knit	
55°	450	

AVAILABLE CYLINDERS LBE45T			
GG75-0,34*	-		
GG70-0,41	340		
GG54-0,50	336		
GG48-0,60	256 - 296		
GG36-0,70	-		

AVAILABLE CYLINDERS LBEST			
GG75-0,34			
GG70-0,41	320 - 376 - 440 - 464		
GG54-0,50	376		
GG48-0,60	288		
GG36-0,70	208		

Above data are indicative and not binding.

\*Needle thick. 0,34 terry only with synthetic fibres.



# WOMEN'S SINGLE CYLINDER LBE45T - LBE5T

#### **NOISE LEVEL**


Machine average noise level, suction included LeqA = 74dBA

#### **LUBRICANTS**

Average consumption for 500/600 dozens: 1000 gr. - Lonati recommends: Fuchs Renolin Trax 14C - Kluber Tex Sintheso M32 - Esso Eil 0287

#### **GREASE**

For seals, bearings etc. Lonati recommends: Damping grease Nyogel 774F




#### FRONT VIEW

Machine dimensions with 40 reels yarn creel

#### NOTE:

The picture may show fittings and equipment that are supplied on demand and not.



#### SIDE VIEW

Machine dimensions with 40 reels yarn creel

#### NOTE:

The picture may show fittings and equipment that are supplied on demand and not.





